

DISPARLON

August 2019

DISPARLON 1970 (Leveling/Defoaming agent)

DISPARLON 1970 is a silicone-free, high molecular weight surface active agent. The product acts as a leveling agent with defoaming effect.

ADVANTAGES

- Imparts leveling, thus minimizing cratering and pinholes.
- Provides smooth film surface with excellent image reflection.
- Releases air that is trapped during paint production and mixing process.
- Eliminates foam produced during coating operation, whether it be from roller coater, flow coater or dipping.
- Does not affect recoatability.

APPLICATIONS

1970 can be used in almost all solvent and High-solids coatings and Automotive coatings.

1970 can also be used in high build Urethanes and Epoxies, where it can also act as a leveling aid.

INCORPORATION

Additive levels : 0.2 ~ 1.0 % by weight on total formulation.
Method : Post addition on high speed dissolver is recommended.

TYPICAL PROPERTIES

Appearance : Colorless to light yellow liquid
Non-volatile matter : 40 % by wt.
Density : 0.92 g/cm³
Solvent : Xylene/ Mineral spirit



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2001 All Rights Reserved By Kusumoto Chemicals, Ltd.