

DISPARLON

May 2019

DISPARLON A603-20X

(Anti-Sagging/Anti-Settling agent)

DISPARLON A603-20X is an alcohol free thixotropic agent developed for isocyanate cured paint systems. Being pre-activated, **A603-20X** can perform as well as 6900-20X just incorporated in the millbase. **A603-20X** is supplied in a paste form.

ADVANTAGES

- Alcohol free, no reaction with isocyanate.
- Strong anti-sagging/settling
- Non-seeding
- No affect on the pot-life.

APPLICATIONS

DISPARLON A603-20X is recommended for isocyanate cured systems such as Polyurethane, Acrylic/Urethane, Tar/Urethane and Epoxy/Urethane Systems.

*Don't use in the oil based systems, such as Alkyd/Melamine and other Alkyd systems.

INCORPORATION

Additive level : 1.0 ~ 5.0 % by weight of total formulation.

Method : Disperse **A603-20X** sufficiently in the millbase using a sand grind mill or a high-speed dissolver.

TYPICAL PROPERTIES

Appearance : White to light yellow paste

Non-volatile matter : 20 % by wt.

Solvent : Xylene



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2001 All Rights Reserved By Kusumoto Chemicals, Ltd.