

Product Data Sheet

K-CORR[®] 1031



Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com

K-CORR 1031 is an ashless rust inhibitor for industrial and automotive lubricants and greases.

CHEMICAL

COMPOSITION: Proprietary carboxylic acid/amide chemistry.

APPEARANCE: Clear amber moderately viscous liquid.

TYPICAL

PROPERTIES:	Nitrogen Content	3.3%
	Viscosity @ 40°C (ASTM D445, DIN 51 550)	1030 mm ² /s (cSt)
	Viscosity @ 100°C (ASTM D445, DIN 51 550)	52 mm ² /s (cSt)
	Density @ 25°C (ASTM D4052)	1.01 g/ml
	Weight Per Gallon @ 25°C	8.4 lbs
	Acid Number, TAN (Potentiometric)	90 mg KOH/g
	Mineral Oil Content	None
	Flash Point, COC (ASTM D92, DIN 51 376)	160°C (320°F)

Note: The above analytical data are not specifications.

		<u>Typical Treat Levels</u>
APPLICATIONS:	Hydraulic Fluids, Ashless (HF-0, HF-2)	0.05% - 0.5%
	Circulating and Compressor Oils	0.05% - 1.0%
	Industrial and Automotive Gear Oils	0.10% - 1.5%
	Paper Machine Oils	0.25% - 1.0%

K-CORR 1031 is a 100% active ashless rust inhibitor with a relatively low acid number compared to succinic acid half esters. **K-CORR 1031** is well suited for formulating ashless rust and oxidation oils, hydraulic oils, paper machine oils and industrial and automotive gear oils. **K-CORR 1031** has excellent solubility in low polarity base oils such as PAO and severely hydrotreated Group II and Group III base oils.

- ADVANTAGES:**
- * Ashless rust inhibitor with an acid number below 100 mg KOH/g
 - * Excellent solubility in low polarity base oils
 - * Good hydrolytic and thermal stability
 - * No detrimental influence on the AFNOR dry and wet filtration tests
 - * No detrimental influence on FZG performance
 - * Synergistic AW performance with selected EP chemistries

(see reverse side)

K-CORR[®] 1031

TEST RESULTS: Technical reports are available from King Industries and can be requested by contacting the offices shown below.

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

STANDARD PACKAGING: 440 lbs (200 kg) closed head drum.

STORAGE CONDITIONS: Formation of haze or crystallization may occur during storage. If this occurs, warming to 40-50°C with agitation will reconstitute the product. Avoid overheating to temperatures above 60°C. Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F).

SHELF LIFE: Best if used within 2 years from the date of manufacture.

HANDLING: Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **K-CORR 1031**.

REGISTRATION: Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

WWW.KINGINDUSTRIES.COM

Global Headquarters

Tech. Services, R&D and Sales

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425

European Tech. Sales Office

King Industries International, Inc.
Science Park 402
1098 XH Amsterdam
The Netherlands
Tel: +31-20-723-1970

China Sales Office

Dalian Mingruida Technical Consulting Co., Ltd
Building 51, 20 Shuxiang Street
Dalian, China
Tel: +86-15941108485

K-CORR[®] is a registered trademark of King Industries, Inc.

v:\lad\TechnicalLiterature\CumtTDS\KCORR\1031_06
Revision date: 27 DEC 2023

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.