

P-Series Defoamers

Defoamers for Floor Coatings & High Viscosity Systems

DISPARLON P-465, P-466, and P-467 are silicone–free defoamers for use in roller and squeegee applied floor coatings. The P-Series was specifically designed for modern high solids and solvent-free flooring formulations including epoxy, polyurethane, and polyaspartics. These formulations are typically applied as thick films with high viscosity making defoaming difficult.

Coating Type	Application	Defoamer Recommendation	Dosage
Ероху	Flooring	P-465	0.5%-1.0%
Urethane	Decks, Roofing	P-466/P-467	0.5%-1.0%
Urethane & Polyaspartic	Flooring	P-465/P-466	0.5%-1.0%

Development Target

Market Trends

High Solids Systems — High Viscosity
Solvent-free Systems

Requires Stronger Defoamer



DISPARLON P-Series P-465, P-466, P-467


Typical Properties					
	P-465	P-466	P-467		
Appearance	Clear to light yellow liquid				
% Active	40%	40%	80%		
Composition	Vinyl polymer				
Solvent	Isoparaffin				

2K Polyurethane Waterproofing Coating












100% Solid Epoxy Fast Cure System









Poor 1 2 3 4 5 Excellent

Contact

Global Headquarters Tech. Service, R&D, and Sales King Industries, Inc. 1 Science Rd. Norwalk, CT 06852

Phone: 1-203-866-5551 www.kingindustries.com

