

# DISPARLON

October 2018

## DISPARLON P-465, P-466, P-467

(Defoaming agent)

DISPARLON P-465, P-466 and P-467 are defoaming agents based on vinyl polymers. These products are characterized by the quick defoaming and long maintained effects in heavy bodied systems such as flooring, waterproofing and paints where existing defoamers are difficult to work.

### ADVANTAGES

- Strong defoaming
- Prevents pinhole and crater
- Promotes air release
- Silicone-free

### APPLICATIONS

DISPARLON P-465, P-466 and P-467 are recommended for floor coatings, heavy duty paints, architectural paints, and waterproof coatings etc.

### INCORPORATION

Additive levels : 0.2 ~ 1.0 % by wt.  
Method : Usually post-added, and dispersed uniformly. When added in pre-mix, a higher level of additive is needed than with post-addition.

### TYPICAL PROPERTIES

	P465	P-466	P-467
Appearance	Clear to light yellow liquid		
Non-volatile matter	40 % by wt.	40 % by wt.	80 % by wt
Solvent	Isoparaffin		
Polarity of Recommended Formulations	High ←————→ Low		



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2018 All Rights Reserved By Kusumoto Chemicals, Ltd.